



Kapasite Aralığı: 10-100 Ton/saat buhar
Basınç: 0-25 Bar
Buhar Sıcaklığı: 120-500 °C
Yakıt: Biokütle ve çeşitli atıklar

Capacity Range: 10-100 Ton/h steam
Pressure: 0-25 Bar
Steam Temperature: 120-500 °C
Fuel: Biomass and various wastes

Özellikler

TR Biyokütle ve endüstriyel atıklar, hareketli ızgaralı sistemlerle yüksek verimle buhar enerjisine dönüştürülür. Kazanlarımız Avrupa'da güvenle kullanılmakta olup uzun ömürlü ve yüksek verimlidir.

Sistemde enerjiye dönüştürülebilen başlıca kaynaklar:

- Orman ve tarım atıkları
- Endüstriyel atıklar
- Arıtma çamuru, hayvansal gübre
- RDF ve ağaç sanayi atıkları

Sertifikalar

PED 2014/68/EU ve uluslararası basınçlı ekipman standartlarına uygundur.

Features

EU Biomass and industrial waste are efficiently converted into steam using moving grate systems. Our boilers are widely used in Europe, offering high efficiency and long service life.

Main energy sources include:

- Forest and agricultural waste
- Industrial residues
- Sludge, animal manure
- RDF and wood industry waste

Certificates

Complies with PED 2014/68/EU and international pressure equipment standards.

Biyokütle ve Biomass Yakıtlı Buhar Kazanları

Biomass Fueled Steam Boilers

