Biomasse-Dampfkessel
Biomass Fueled Steam Boilers



Dampfleistung:	10–100 t/h
Druck:	0–25 bar
Dampftemp.:	120–500 °C
Brennstoff:	Biomasse und verschiedene Abfälle

Capacity Range:	10-100 Ton/h steam
Pressure:	0-25 Bar
Steam Temperature:	120-500 °C
Fuel:	Biomass and various wastes

DE

Merkmale

Die Kessel verbrennen Biomasse und Industrieabfälle auf einem beweglichen Rost und erzeugen dabei mit hohem Wirkungsgrad Dampf. Unsere langlebigen, hocheffizienten Kessel sind in Europa im Einsatz.

Wesentliche verwertbare Stoffe:

- Forst- und Agrarreststoffe
- Industrieabfälle
- Klärschlamm und tierischer Wirtschaftsdünger
- Ersatzbrennstoffe (EBS/RDF) und Holzindustrieabfälle

Zertifizierung

Konform mit der Druckgeräterichtlinie 2014/68/EU und den einschlägigen internationalen Normen für Druckgeräte.

EN

Features

Biomass and industrial waste are efficiently converted into steam using moving grate systems. Our boilers are widely used in Europe, offering high efficiency and long service life. Main energy sources include:

- Forest and agricultural waste
- Industrial residues
- Sludge, animal manure
- RDF and wood industry waste

Certificates

Complies with PED 2014/68/EU and international pressure equipment standards.

Biomasse-Dampfkessel
Biomass Fueled Steam Boilers



