



CODE	MODELL	BEHÄLTERABM. (mm) (Ø × Gesamthöhe)	ANSCHLÜSSE (DN, FLANSCH) BETRIEB / ABLAUF	BETRIEBSDURCHFLUSS (m³/h)		FILTERMEDIEN	
				Geschwindigkeit: 20 m/h	Geschwindigkeit: 30 m/h	ANTHRAZIT (lt)	QUARTZ (kg)
50400000	F-3072	775 x 2050	50 - 50	9	14	140	475
50400005	F-3672	975 x 2150	50 - 50	13	20	175	650
50400010	F-4272	1075 x 2400	65 - 65	18	27	210	775
50400015	F-4872	1225 x 2400	65 - 65	23	35	315	1125
50400020	F-6386	1600 x 2500	80 - 80	40	60	560	2025

DE

Merkmale

- GFK-Behälter der Marke WCY
- Maximaler Betriebsdruck: 6 bar
- Zeitgesteuerte Rückspülung
- Absperrklappen mit Elektroantrieb (pneumatisch ohne Aufpreis)
- Bodensammler mit radialem Verteiler
- Außenverrohrung aus PVC-U auf epoxidbeschichtetem Rahmen
- Probenahmehähne und Manometer an Ein- und Auslauf
- Elektronischer Steuerschrank
- Versorgung: 220 V / 50 Hz, einphasig
- Trockene Instrumentenluft für die Ventile ist bauseits bereitzustellen. Empfohlene Kompressorleistung: mindestens 100 L/min bei 8 bar.

EN

Features

- WCY brand FRP tank
- Maximum operating pressure: 6 bar
- Time-controlled backwashing
- Electric actuator butterfly valves

(No price difference if pneumatic actuator is used)

- Bottom collection system with octopus diffuser
- PVC-U material surface piping (Epoxy painted gas surface)
- Sample taps and pressure gauges at system inlet and outlet
- Electronic card control panel
- Electrical: 220V / 50 Hz / 1 phase
- The supply of dry instrument air required for the operation of pneumatic valves is the responsibility of the customer. The recommended compressor capacity is a minimum of 100 L/min @ 8 bar.