Filtro a sabbia
Sand Filter





CODICE	MODELLO	DIM. SERBATOIO (mm) (Ø × altezza tot.)	ATTACCHI (DN, FLANGIA) SERVIZIO / SCARICO	PORTATA DI SERVIZIO (m³/h) Velocità: 20 m/h	PORTATA DI SERVIZIO (m³/h) Velocità: 30 m/h	MATERIALI FILTRANTI ANTRACITE (lt)	MATERIALI FILTRANTI QUARTZ (kg)
50400000	F-3072	775 x 2050	50 - 50	9	14	140	475
50400005	F-3672	975 x 2150	50 - 50	13	20	175	650
50400010	F-4272	1075 x 2400	65 - 65	18	27	210	775
50400015	F-4872	1225 x 2400	65 - 65	23	35	315	1125
50400020	F-6386	1600 x 2500	80 - 80	40	60	560	2025

IT

Caratteristiche

- Serbatoio in vetroresina (PRFV) WCY
- Pressione massima di esercizio di 6 bar
- Controlavaggio temporizzato
- Valvole a farfalla con attuatore elettrico (opzione pneumatica senza sovrapprezzo)
- Collettore inferiore con diffusore radiale
- Tubazioni esterne in PVC-U su telaio con rivestimento epossidico
- Rubinetti di prelievo e manometri su ingresso e uscita
- Quadro di controllo elettronico
- Alimentazione monofase: 220 V / 50 Hz
- L'aria secca per le valvole pneumatiche è a carico del cliente. Portata minima consigliata del compressore: 100 L/min a 8 bar.

EN

Features

- WCY brand FRP tank
- Maximum operating pressure: 6 bar
- Time-controlled backwashing
- Electric actuator butterfly valves

(No price difference if pneumatic actuator is used)

- Bottom collection system with octopus diffuser
- PVC-U material surface piping (Epoxy painted gas surface)
- Sample taps and pressure gauges at system inlet and outlet
- Electronic card control panel
- Electrical: 220V / 50 Hz / 1 phase
- The supply of dry instrument air required for the operation of pneumatic valves is the responsibility of the customer. The recommended compressor capacity is a minimum of 100 L/min @ 8 bar.