Паровые котлы на биомассе
Biomass Fueled Steam Boilers



Выработка пара:	10–100 т/ч
Давление:	0–25 бар
Темп. пара:	120–500 °C
Топливо:	Биомасса и различные отходы

Capacity Range:	10-100 Ton/h steam
Pressure:	0-25 Bar
Steam Temperature:	120-500 °C
Fuel:	Biomass and various wastes

RU

Особенности

Котлы с подвижной колосниковой решёткой эффективно вырабатывают пар за счёт сжигания биомассы и промышленных отходов. Наши долговечные и высокоэффективные котлы применяются в Европе.

Основное сырьё для получения энергии:

- Отходы лесного и сельского хозяйства
- Промышленные отходы
- Осадки очистных сооружений и навоз
- Топливо RDF и отходы деревообработки

Сертификация

Соответствует PED 2014/68/EU и международным стандартам для оборудования под давлением.

EN

Features

Biomass and industrial waste are efficiently converted into steam using moving grate systems. Our boilers are widely used in Europe, offering high efficiency and long service life. Main energy sources include:

- Forest and agricultural waste
- Industrial residues
- Sludge, animal manure
- RDF and wood industry waste

Certificates

Complies with PED 2014/68/EU and international pressure equipment standards.

Паровые котлы на биомассе
Biomass Fueled Steam Boilers



