Akışkan Yataklı Kızgın Yağ Kazanı
Fluidized Bed Thermal Oil Boiler



AKIŞKAN YATAKLI KIZGIN YAĞ KAZANI

Kapasite Aralığı:	3-15.000.000 KCAL kızgın yağ
Kızgın Yağ Sıcaklığı:	0-270 °C
Yakıt:	0-16mm (1.500-6.000 kcal) aralığında kömür
Avantaj:	%90 Yanma verimi
Filtrasyon:	Elektrostatik ve torbalı filtre seçeneği

AKIŞKAN YATAKLI KOMBİNE KAZANI

Kapasite Aralığı:	5-20 Ton/saat buhar
Kızgın Yağ Kapasitesi:	2-10.000.000 KCAL kızgın yağ
Basınç:	0-8 Bar
Kızgın Yağ Sıcaklığı:	0-270 °C
Yakıt:	0-16mm (1.500-6.000 kcal) aralığında kömür
Avantaj:	%90 Yanma verimi
Filtrasyon:	Elektrostatik ve torbalı filtre seçeneği

FLUIDIZED BED HOT OIL BOILER

Capacity Range:	3-15.000.000 KCAL hot oil
Hot Oil Temperature:	0-270 °C
Fuel:	0-16mm (1.500-6.000 kcal) coal in range
Advantage:	%90 Burning efficiency
Filtration:	Electrostatic and bag filter option

FLUIDIZED BED COMBINED BOILER

Capacity Range:	5-20 Ton/h steam
Hot Oil Capacity:	2-10.000.000 KCAL hot oil
Pressure:	0-8 Bar
Hot Oil Temperature:	0-270 °C
Fuel:	0-16mm (1.500-6.000 kcal) coal in range
Advantage:	%90 Burning efficienty
Filtration:	Electrostatic and bag filter option

Özellikler

TR

Akışkan yataklı kızgın yağ kazanlarımız düşük kalorili, yüksek kül oranında linyit kömürleri %85 verimle yakabilen bir sisteme sahip kazan çeşididir. Özellikle yağ, tekstil, kimya gibi yüksek sıcaklık gerektiren proseslerde kullanılmaktadır. Bubbling ve sirkülasyonlu tiplerini üretmekteyiz. Kullanılan filtre sistemleri sayesinde partikül ve gaz salınımı olarak çevre yönetmeliği standartlarına uygundur.

Sertifikalar

PED 2014/68/EU ve ilgili uluslararası basınçlı ekipman standartlarına uygun olarak tasarlanmış ve üretilmiştir.

Features

EN

Our fluidized bed thermal oil boilers are designed to burn low-calorific, high-ash lignite coals with up to 85% efficiency. These boilers are particularly used in high-temperature processes such as in the oil, textile, and chemical industries. We manufacture both bubbling and circulating types. Thanks to the filtration systems used, the boilers comply with environmental regulation standards in terms of particulate and gas emissions.

Certificates

Designed and manufactured in compliance with PED 2014/68/EU and relevant international pressure equipment standards.